

<b>HPR-02</b>		<b>55</b>	<b>75</b>	<b>105</b>	<b>135</b>	<b>165</b>	<b>210</b>	<b>105D</b>	<b>280</b>	<b>125D</b>	<b>165D</b>
Max. displacement	cc/rev	55	75.9	105	135.7	165.6	210.1	210	281.9	252	331.2
Continuous rated speed w/o pressurizing	rpm	2700	2500	2350	2300	2100	2000	2350	1800	2300	2100
Max. oil flow	l/min	148.5	189.8	246.8	312.1	347.8	420.2	493.5	507.4	579.6	695.5
Nominal pressure	bar	420	420	420	420	420	420	420	420	350	420
Peak pressure (Intermittent)	bar	500	500	500	500	500	500	500	500	420	500
Continuous input torque	Nm	218	302	418	540	659	836	836	1122	1003	1318
Max. input torque	Nm	368	507	702	907	1107	1404	1245	1884	1404	1964
Continuous power	kW	61.9	79.1	102.8	130	144.9	175.1	205.6	211.4	241.5	289.8
Max. power	kW	104	132.8	172.7	218.5	243.4	294.1	306.7	355.2	338.1	431.8
Weight (approx.)	kg	39	39	50	65	89	116	96	165	113	177